

KEYED MECHANICAL NOTES: (X)

1. TO WALL-1 ON ROOF. SEE SHEET M1.3. SEAL PENETRATION THRU WALL WEATHER TIGHT.
2. TO RTU-4 ON ROOF. SEE SHEET M1.3. SEAL PENETRATION THRU WALL WEATHER TIGHT.
3. TO RTU-5 ON ROOF. SEE SHEET M1.3. SEAL PENETRATION THRU WALL WEATHER TIGHT.
4. TO RTU-5 ON ROOF. SEE SHEET M1.3. SEAL PENETRATION THRU WALL WEATHER TIGHT.
5. TO ERV-1 ON ROOF. SEE SHEET M1.3. SEAL PENETRATION THRU WALL WEATHER TIGHT.
6. UP TO RTU-2 ON ROOF. SEE SHEET M1.3.
7. UP TO RTU-3 ON ROOF. SEE SHEET M1.3.
8. MOUNT TOP OF CUH AT 42' A.F.F.
9. MOUNT TOP OF UH AT 8'-0" A.F.F.
10. SEE SHEET M1.2 FOR CONTINUATION.
11. COORDINATE DUCT MOUNTING HEIGHT WITH OVERHEAD DOOR ELEVATION.
12. COORDINATE UH MOUNTING HEIGHT WITH OVERHEAD DOOR ELEVATION.
13. MOUNT TOP OF FC-1 AT 9'-0" A.F.F.
14. PROVIDE AND INSTALL 60"X60" LOUVER WITH INSECT SCREEN SIMILAR TO UNITED ENERTECH FL-4 OR EQUAL. PROVIDE WITH 120 V ACTUATOR DAMPER. INTERLOCK DAMPER WITH EF-10. MOUNT TOP OF LOUVER AT 10'-0" A.F.F. INTERLOCK WITH WALL SWITCH AND TIME. PROVIDE END SWITCH ON DAMPER.
15. MOUNT TOP OF LTD AT 8'-0" A.F.F.
16. 10' COMBUSTION AIR DUCT UP THROUGH ROOF.
17. 8" BOILER FLUE UP THROUGH ROOF.
18. CONCENTRIC TERMINATION VENT FROM WATER HEATER UP THROUGH ROOF.
19. INTERLOCK WITH WALL SWITCH.
20. BOILER EMERGENCY SHUT OFF SWITCH.


X
W
V
U
T
S
R
Q
P
O
N
M
L
K
J
H
G
F
E
D
C
B
A

GENERAL NOTES:


1. PROVIDE TURNING VANES IN ALL 90° ELBOWS.
2. MOUNT THERMOSTATS AT 48" A.F.F.

NOT DISCLOSED

1 ENLARGED MECHANICAL PLAN - NORTH
1/8" = 1'-0"



Printed On:




KEYED MECHANICAL NOTES: (X)


1. COORDINATE DUCT MOUNTING HEIGHT WITH OVERHEAD DOOR AND CRANE TRAVEL.
2. COORDINATE UH MOUNTING HEIGHT WITH OVERHEAD DOOR TRAVEL AND OVERHEAD CRANE.
3. SEE SHEET M-1 FOR CONTINUATION.
4. MOUNT TOP OF UH @ 96" A.F.F.
5. MOUNT BOTTOM OF ACC-1 @ 12'-0" A.F.F. PROVIDE WALL MOUNT BRACKET.
6. BALANCE OUTSIDE AIR TO 100 CFM. INSULATE OUTSIDE AIR DUCT WITH 2" FOIL FACED FIBERGLASS INSULATION.
7. INTERLOCK MOTORIZED DAMPER WITH AHU-1. DAMPER SHALL OPEN WHEN FAN IS ENERGIZED. DAMPER SHALL CLOSE WHEN FAN IS DE-ENERGIZED.
8. ROUTE RURS LINES SET TO AHU-1. RACK PIPING ON WALL.
9. ROUTE POWER WASHER FLUE THROUGH ROOF WITH TYPE B FLUE VENT. SEE FLUE PIPING DETAIL. INSTALL FLUE PER MANUFACTURER'S RECOMMENDATIONS.
10. PROVIDE AND INSTALL TOXIC GAS DETECTION SYSTEM CONTROLLER, HONEYWELL MODEL "301C" OR SIMILAR. PROVIDE LOW VOLTAGE TRANSFORMER SIZED FOR ENTIRE GAS DETECTION SYSTEM. PROVIDE PANEL DP-1; MOUNT CONTROLLER AND TRANSFORMER IN PANEL. SEE ELEC PLANS FOR 110V POWER TO PANEL.
11. PROVIDE LOW VOLTAGE CONTROL WIRING IN CONDUIT FROM GAS DETECTION CONTROLLER 301C TO RELAYS FOR EXHAUST FANS. THESE RELAYS ARE PROVIDED/INSTALLED BY ELEC CONTRACTOR. SEE ELEC PLANS FOR RELAY LOCATION AND NOTE ELECTRIC CONTRACTOR IS PROVIDING A "FAN ON" SWITCH FOR EACH EXHAUST FAN TO ALLOW USER CONTROLLED SUMMER EXHAUST VENTILATION.
12. PROVIDE AND INSTALL HONEYWELL E3POINT (OR SIMILAR) "E3SM" SENSOR MONITOR UNIT (SMU) WITH "E3SCO" CARBON MONOXIDE (CO) SENSOR CARTRIDGE, ON-BOARD ANNUNCIATOR, AND REMOTE MOUNTED STROBE LIGHT. MOUNT "CO" SMU AT 5 FT A.F.F. PROVIDE LOW VOLTAGE POWER WIRING TO EACH SMU, STROBE WIRING BACK TO SMU, AND DAISY-CHAIN COMM. WIRING FROM THE SMU'S BACK TO GAS DETECTION CONTROLLER IN PANEL DP-1 (ALL WIRING IN CONDUIT).
13. PROVIDE AND INSTALL HONEYWELL E3POINT (OR SIMILAR) "E3SM" SENSOR MONITOR UNIT (SMU) WITH "E3NO2" NITROGEN DIOXIDE (NO₂) SENSOR CARTRIDGE, ON-BOARD ANNUNCIATOR, AND REMOTE MOUNTED STROBE LIGHT. MOUNT "NO₂" SMU AT HEIGHT RECOMMENDED BY MANUFACTURER. PROVIDE LOW VOLTAGE POWER WIRING TO EACH SMU, STROBE WIRING BACK TO SMU, AND DAISY-CHAIN COMM. WIRING FROM THE SMU'S BACK TO GAS DETECTION CONTROLLER IN PANEL DP-1 (ALL WIRING IN CONDUIT).
14. PROVIDE AND INSTALL HONEYWELL E3POINT (OR SIMILAR) "E3SM" SENSOR MONITOR UNIT (SMU) WITH "E3M" COMPRESSED NATURAL GAS (CNG) SENSOR CARTRIDGE, ON-BOARD ANNUNCIATOR, AND REMOTE MOUNTED STROBE LIGHT. MOUNT "CNG" SMU AT HEIGHT RECOMMENDED BY MANUFACTURER. PROVIDE LOW VOLTAGE POWER WIRING TO EACH SMU, STROBE WIRING BACK TO SMU, AND DAISY-CHAIN COMM. WIRING FROM THE SMU'S BACK TO GAS DETECTION CONTROLLER IN PANEL DP-1 (ALL WIRING IN CONDUIT).
15. RANGE OF SENSOR MONITOR UNIT (SMU) IS A 50 FT RADIUS CIRCLE. INSTALL SMU PER MANUFACTURER'S SPECIFICATIONS AND RECOMMENDATIONS.
16. NOT USED.
17. NOT USED.
18. UPON DETECTION OF ELEVATED LEVELS OF CO, NO₂, OR CNG, GAS DETECTION SYSTEM SHALL INCREASE EXHAUST FAN AND MAKE-UP AIR UNIT FAN SPEED FROM LOW SPEED TO MAX SPEED.
19. EXHAUST FAN EQUIPPED WITH GRAVITY BACKDRAFT DAMPER (NOT MOTORIZED).

GENERAL NOTES:

1. PROVIDE TURNING VANES IN ALL 90° ELBOWS.
2. MOUNT THERMOSTATS AT 48" A.F.F.

NOT DISCLOSED






1 ENLARGED MECHANICAL PLAN - ROOF
1/8" = 1'-0"

KEYED MECHANICAL NOTES: (X)

1. 4"Ø FLUE FROM GAS WATER HEATER.
2. 8" FLUE FROM BOILER.
3. 10" COMBUSTION AIR FOR BOILER.
4. 4" VTR.
5. PRESSURE WASHER FLUE THROUGH ROOF. PROVIDE WITH TYPE B ROOF CAP.
6. UPON DETECTION OF ELEVATED LEVELS OF CO, NO₂, OR CNG, GAS DETECTION SYSTEM SHALL INCREASE EXHAUST FAN AND MAKE-UP AIR UNIT FAN SPEED FOR LOW SPEED TO MAX SPEED.
7. SEE M1.1 FOR CONTINUATION.






2 MECHANICAL PLAN - ROOF
1/16" = 1'-0"

NOT DISCLOSED

MECHANICAL PLAN - ROOF

Sheet No. | M1.3





ENLARGED MECHANICAL ROOM PLAN
SCALE: 1/4" = 1'-0"

NOTE:
3/4" HWS, 3/4" HWR TO VAV-1
THRU 13 & 15 COILS.
1" HWS, 1" HWR TO VAV-14
1" HWS, 1" HWR TO HC-1
3/4" HWS, 3/4" HWR TO HC-2
1 1/4" HWS, 1 1/4" HWR TO HC-3
1 1/2" HWS, 1 1/2" HWR TO HC-4

IN-FLOOR HEATER ALTERNATE NO. 2
150.38 MBH, 7519 SQ. FT., 20 BTU/SQ. FT.
2 ZONES, 24 CIRCUITS @ 12" SPACING, 0.84 GPM
PER CIRCUIT, 330' MAX. TUBE LENGTH @
15.07' HEAD LOSS, 9.50 GPM TOTAL. COORDINATE
MANIFOLD LOCATIONS WITH OWNER.

IN-FLOOR HEATER ALTERNATE NO. 1
71.31 MBH, 2377 SQ. FT., 30 BTU/SQ. FT.
8 CIRCUITS @ 12" SPACING, 1.18 GPM
PER CIRCUIT, 330' MAX. TUBE LENGTH @
15.07' HEAD LOSS, 9.50 GPM TOTAL. COORDINATE
MANIFOLD LOCATIONS WITH OWNER.


- KEYED PIPING NOTES: (X)
- 3/4" HWS DN, 3/4" HWR DN. SEE CABINET UNIT HEATER PIPING DETAIL ON SHEET M2.2.
 - 1" HWS DN, 1" HWR DN. SEE UNIT HEATER PIPING DETAIL ON SHEET M2.2.
 - FILTER FEEDER. SEE BASE MOUNTED PUMP DETAIL ON SHEET M2.2 FOR PIPING.
 - 60 GALLON THERMAL EXPANSION TANK. SUSPENDED FROM STRUCTURE ABOVE PUMPS. SEE DETAIL ON SHEET M2.2. BASED ON 20.8 GALLONS OF EXPANSION, 0.37 ACCEPTANCE FACTOR, OPERATING WEIGHT 629 LBS. TACO MODEL PS200-125 OR EQUAL.
 - BASE MOUNTED CIRCULATING PUMP ON CONCRETE HOUSEKEEPING PAD. HOUSEKEEPING PAD BY OTHERS. SEE PUMP DETAIL ON SHEET P1.7.
 - FLANGED AIR SEPARATOR. TACO MODEL AC03-150.
 - GAS FIRED BOILER ON CONCRETE HOUSEKEEPING PAD. HOUSEKEEPING PAD BY OTHERS.
 - PROVIDE AND INSTALL 3-WAY VALVE.
 - AUTOMATIC GLYCOL FEED PACKAGE. SHALL BE MANUFACTURED BY GENERAL TREATMENT PRODUCTS MODEL: GP-56-E-2, OR APPROVED EQUAL AND CONSIST OF A 55 GAL POLYETHYLENE TANK, HINGED POLYETHYLENE COVER, CARBON STEEL FRAME, LOCKABLE NEMA 4X CONTROL PANEL, LOW LEVEL FLOAT SWITCH, 1/3 HP (115/1, 5.6 AMP) OPEN MOTOR BRONZE GEAR PUMP WITH INTERNAL PRESSURE RELIEF, PRESSURE SWITCH, PRESSURE RELIEF VALVE, CHECK VALVE, Y STRAINER, PVC PLUMBING AND REINFORCED BUTYL RUBBER HOSE ASSEMBLIES.


- GENERAL NOTES:
- THE IN-FLOOR HEAT ENTERING WATER TEMPERATURE SHALL BE SET AT 100°F.
 - THE DESIGN SHALL BE BASED ON A 15° DELTA T.
 - THE DESIGN SHALL BE BASED ON 60° PEX TUBING.
 - PIPE SPACING SHALL BE SET AT 12" ON CENTER.
 - THE PRESSURE DROP IS BASED ON 30% PROPYLENE GLYCOL @ 60° START UP TEMPERATURE.
 - TOTAL HEAD PRESSURE SHOWN INCLUDES PRESSURE DROP THROUGH THE IN-FLOOR HEAT MANIFOLD.
 - THE PIPING IN THE SHOP AND ANY EXPOSED AREAS SHALL HAVE A PROTECTIVE PVC JACKETED SHELL INSULATION.
 - UNDERSLAB IN-FLOOR HEAT INSULATION BY OTHERS.
 - PROVIDE PROPYLENE GLYCOL CLEANING, FLUSHING AND TESTING RESULTS WITH PROJECT O&M MANUALS.

1 HYDRONIC PIPING PLAN - NORTH
1/8" = 1'-0"

NOT DISCLOSED

HYDRONIC PIPING PLAN - NORTH





IN-FLOOR HEAT ZONE NO. 8
 25.1 MBH, 717 SQ. FT. 35 BTU/SQ.FT.
 3 CIRCUITS @ 12" SPACING, 1.1 GPM
 PER CIRCUIT, 330' MAX TUBE LENGTH @
 13.51' HEAD LOSS 3.34 GPM TOTAL

IN-FLOOR HEAT ZONE NO. 11
 31.74 MBH, 1090 SQ. FT. 30 BTU/SQ.FT.
 4 CIRCUITS @ 12" SPACING, 1.16 GPM
 PER CIRCUIT, 330' MAX TUBE LENGTH @
 12.50' HEAD LOSS 4.23 GPM TOTAL

IN-FLOOR HEAT ZONE NO. 3
 76.32 MBH, 2544 SQ. FT. 30 BTU/SQ.FT.
 8 CIRCUITS @ 12" SPACING, 1.27 GPM
 PER CIRCUIT, 330' MAX TUBE LENGTH @
 16.80' HEAD LOSS 10.16 GPM TOTAL

IN-FLOOR HEAT ZONE NO. 4
 77.94 MBH, 2698 SQ. FT. 30 BTU/SQ.FT.
 8 CIRCUITS @ 12" SPACING, 1.29 GPM
 PER CIRCUIT, 330' MAX TUBE LENGTH @
 17.24' HEAD LOSS 10.33 GPM TOTAL

IN-FLOOR HEAT ZONE NO. 5
 112.29 MBH, 3743 SQ. FT. 30 BTU/SQ.FT.
 12 CIRCUITS @ 12" SPACING, 1.24 GPM
 PER CIRCUIT, 330' MAX TUBE LENGTH @
 16.22' HEAD LOSS 14.97 GPM TOTAL

IN-FLOOR HEAT ZONE NO. 6
 87.48 MBH, 2597 SQ. FT. 30 BTU/SQ.FT.
 8 CIRCUITS @ 12" SPACING, 1.14 GPM
 PER CIRCUIT, 330' MAX TUBE LENGTH @
 17.27' HEAD LOSS 11.95 GPM TOTAL

IN-FLOOR HEAT ZONE NO. 7
 87.47 MBH, 2596 SQ. FT. 30 BTU/SQ.FT.
 8 CIRCUITS @ 12" SPACING, 1.25 GPM
 PER CIRCUIT, 330' MAX TUBE LENGTH @
 17.27' HEAD LOSS 11.95 GPM TOTAL

IN-FLOOR HEAT ZONE NO. 1
 21.39 MBH, 713 SQ. FT. 30 BTU/SQ.FT.
 3 CIRCUITS @ 12" SPACING, 0.95 GPM
 PER CIRCUIT, 330' MAX TUBE LENGTH @
 10.77' HEAD LOSS 2.85 GPM TOTAL

IN-FLOOR HEAT ZONE NO. 2
 77.88 MBH, 1947 SQ. FT. 40 BTU/SQ.FT.
 7 CIRCUITS @ 12" SPACING, 1.48 GPM
 PER CIRCUIT, 330' MAX TUBE LENGTH @
 21.32' HEAD LOSS 10.38 GPM TOTAL

IN-FLOOR HEAT ZONE NO. 9
 8.86 MBH, 253 SQ. FT. 35 BTU/SQ.FT.
 1 CIRCUIT @ 12" SPACING, 1.18 GPM
 PER CIRCUIT, 330' MAX TUBE LENGTH @
 15.01' HEAD LOSS 1.18 GPM TOTAL

IN-FLOOR HEAT ZONE NO. 10
 9.45 MBH, 271 SQ. FT. 35 BTU/SQ.FT.
 1 CIRCUIT @ 12" SPACING, 1.26 GPM
 PER CIRCUIT, 380' MAX TUBE LENGTH @
 18.64' HEAD LOSS 1.26 GPM TOTAL


GENERAL NOTES:

1. THE IN-FLOOR HEAT ENTERING WATER TEMPERATURE SHALL BE SET AT 100°F.
2. THE DESIGN SHALL BE BASED ON A 15' DELTA T.
3. THE DESIGN SHALL BE BASED ON 5/8" PEX TUBING.
4. PIPE SPACING SHALL BE SET AT 12" ON CENTER.
5. THE PRESSURE DROP IS BASED ON 30% PROPYLENE GLYCOL @ 80° START UP TEMPERATURE.
6. TOTAL HEAD PRESSURE SHOWN INCLUDES PRESSURE DROP THROUGH THE IN-FLOOR HEAT MANIFOLD.
7. THE PIPING IN THE SHOP AND ANY EXPOSED AREAS SHALL HAVE A PROTECTIVE PVC JACKETED SHELL INSULATION.
8. UNDERSLAB IN-FLOOR HEAT INSULATION BY OTHERS.
9. PROVIDE PROPYLENE GLYCOL, CLEANING, FLUSHING AND TESTING RESULTS WITH PROJECT O&M MANUALS.

KEYED PIPING NOTES: (X)

1. 3/4" HWR DN, 3/4" HWS DN. SEE IN-FLOOR HEAT MANIFOLD DETAIL ON SHEET M2.2.
2. 1 1/4" HWR DN, 1 1/4" HWS DN. SEE IN-FLOOR HEAT MANIFOLD DETAIL ON SHEET M2.2.
3. 3/4" HWS DN, 3/4" HWR DN. SEE UNIT HEATER PIPING DETAIL ON SHEET M2.2.
4. 1" HWS DN, 1" HWR DN. SEE IN-FLOOR HEAT MANIFOLD DETAIL ON SHEET M2.2.
5. SEE CONTINUATION ON SHEET P1.6.
6. PROVIDE AND INSTALL 3-WAY VALVE.

NOT DISCLOSED



HOT WATER COIL table with columns: MARK, RTU-S, CFM, COIL SIZE, FINS/IN, NU. OF ROWS, MAX. FAN SPEED, MAX. AIR PD, TOTAL CAP., EAT (°F), LAT (°F), GPM, MAX. WATER PD, EWT (°F), LWT (°F), MANUFACTURE, MODEL, NOTES

NOTES: 1. PROVIDE WITH DELTA FLO FINS.

DIFFUSER, REGISTERS, AND GRILLES

Table with columns: MARK, MAX STATIC PD, MAX NC, DAMPER, FRAME TYPE, NECK SIZE, FACE SIZE, MOUNTING, MATERIAL, FINISH, MANUFACTURE, MODEL, NOTES

NOTES: 1. CONTRACTOR SHALL VERIFY MOUNTING, FINISH AND SURFACE CONSTRUCTION PRIOR TO FURNISHING MATERIALS. 2. NC SHALL BE LESS THAN 20 ON DIFFUSERS, REGISTERS, AND GRILLES LOCATED IN OCCUPIED SPACES.

TERMINAL BOX - HOT WATER REHEAT

Table with columns: MARK, MIN, MAX COOLING, MAX HEATING, MAX PRESSURE DROP, MAX NC, INLET DIAMETER, SIZE, WEIGHT, CAPACITY, EAT/LAT, ROWS, GPM, WATER PD, MANUFACTURE, MODEL, NOTES

NOTES: 1. PROVIDE WITH DDC CONTROLS, COIL ACCESS PANEL. FIELD VERIFY RIGHT OR LEFT HAND UNIT.

UNIT HEATER SCHEDULE

Table with columns: UNIT NO., MFG, MODEL NO., TYPE, INTAKE LOCATION, DISCHARGE FAN, FAN MOTOR(S), HEATING CAPACITY, REMARKS

MODEL TYPE: F - FLOOR; FI - FLOOR INVERTED FLOW; W - WALL; WI - WALL INVERTED FLOW; FRW - FULLY RECESSED WALL; FRWI - FULLY RECESSED WALL INVERTED FLOW; SRW - SEMI RECESSED WALL; SRWI - SEMI RECESSED WALL INVERTED FLOW; C - CEILING; RC - RECESSED CEILING; H - HORIZONTAL PROPELLER UNIT; VP - VERTICAL PROPELLER UNIT

REMARKS: 1. HEATING CAPACITY BASED ON 75% WATER/ 25% PROPYLENE GLYCOL. 2. PROVIDE TAMPER RESISTANT FASTENERS FOR ACCESS DOOR. 3. HANG UNIT FROM STRUCTURE WITH NEOPRENE ISOLATORS. 4. INSTALL TOP OF HEATER +/- 6" BELOW MEZZANINE. 5. INSTALL 2" BELOW STRUCTURAL STEEL. VERIFY UNIT DOES NOT INTERFERE WITH CRANE OPERATION.

PUMP SCHEDULE

Table with columns: UNIT NO., MFG, DESCRIPTION, MODEL NO., FLANGE SIZE, IMPELLER STYLE, FLOW RATE, HEAD, MOTOR HP, RPM, ELECTRICAL VPH, FLA, REMARKS

REMARKS: 1. PUMPS SHALL BE MOUNTED IN A MANNER THAT WILL ALLOW THEM TO BE EASILY SERVICED AND/OR REPLACED. 2. PUMP SELECTION IS BASED ON 25% PROPYLENE GLYCOL @ 80° STARTUP TEMP.

ENERGY RECOVERY VENTILATOR (WITH TOTAL ENERGY WHEEL) table with columns: MARK, MIN. OA, MAX. CA, MIN. E.A., MAX. E.A., S.A. CFM, SUPPLY ESP, EXHAUST ESP, ENERGY RECOVERY WHEEL SUMMER, ENERGY RECOVERY WHEEL WINTER, WHEEL EFF, COOLING SECTION, HEATING SECTION, HOT GAS REHEAT, ELECTRICAL DATA, GENERAL DATA, MANUFACTURE, MODEL, NOTES

NOTES: 1. DESIGN CONDITIONS BASED ON SUMMER DB 95°F AND WB 79°F, AND WINTER DB -20° F. 2. PROVIDE ROOF CURB, MODULATING WHEEL FROST CONTROL, MERV 8 OA, EA AND SUPPLY AIR FILTERS, OA, EA AND SUPPLY LOW LINK DAMPERS, SUPPLY AND EXHAUST VFDs, BAGNET CONTROLLER, PHASE AND BROWN OUT PROTECTION, UNIT DISCONNECT, HAIL GUARDS, R-10A REFRIGERANT, VARIABLE CAPACITY DIGITAL SCROLL COMPRESSOR, CRANKCASE HEATER, ECM CONDENSING FAN MOTOR, HIGH AND LOW PRESSURE CUTOUTS, SERVICE VALVES AND STAINLESS STEEL HEAT EXCHANGER WITH POWER VENTING.

MAKE UP AIR UNIT - GAS FIRED table with columns: MARK, TYPE, CFM, RPM, EXTERNAL SP, TEMP, CAPACITY, ELECTRICAL DATA, WEIGHT, MANUFACTURE, MODEL, NOTES

NOTES: 1. PROVIDE ROOF CURB WITH VIBRATION ISOLATION, VARIABLE VOLUME TWO SPEED CONTROL (39,100 CFM ALARM, NORMAL 19,555 CFM), ALUMINUM MESH WEATHER-HOOD, ANGLED FILTER SECTION (MERV-8 FILTERS), EXTENDED LUBE LINES, FACTORY MOUNTED VFD, HEAT INLET AIR SENSOR, DIRTY FILTER SWITCH, FIRE STAT (TYPE III), SMOKE DETECTOR, BMS INTERFACE (MONITOR ONLY, BACNET/PI) AND HINGED ACCESS PANELS.

ROOFTOP UNIT SCHEDULE

Table with columns: MARK, BLOWER, COOLING, CAPACITY, ELECTRICAL DATA, WEIGHT, MANUFACTURE, MODEL, NOTES

NOTES: 1. NOT USED. 2. PROVIDE WITH INTEGRAL BACKDRAFT DAMPER, DISCONNECT, RECTANGULAR HOODED WALL CAP (WC-18XB), WHITE ALUMINUM GRILLE, ROUND DUCT CONNECTOR AND ALUMINUM WHEEL. 3. PROVIDE WITH INTEGRAL SPRING LOADED BACKDRAFT DAMPER, DISCONNECT, RECTANGULAR HOODED WALL CAP (WC-18XB) AND ALUMINUM WHEEL.

FANS

Table with columns: MARK, LOCATION, FAN DATA, MOTOR DATA, MANUFACTURE, MODEL, NOTES

NOTES: 1. PROVIDE WITH INTEGRAL BACKDRAFT DAMPER, DISCONNECT, RECTANGULAR HOODED WALL CAP (WC-10X3), WHITE ALUMINUM GRILLE, ROUND DUCT CONNECTOR AND ALUMINUM WHEEL. 2. PROVIDE WITH INTEGRAL SPRING LOADED BACKDRAFT DAMPER, DISCONNECT, RECTANGULAR HOODED WALL CAP (WC-18XB) AND ALUMINUM WHEEL.

UNIT HEATER - HYDRONIC

Table with columns: MARK, LOCATION, WT., CFM, EAT, LAT, EWT, LWT, MBH, DELTA P, MBH, ELECTRIC DATA, CABINET DATA, MANUFACTURE, MODEL, NOTES

NOTES: 1. INSTALL 2" BELOW STRUCTURAL STEEL. VERIFY UNIT HEATER DOES NOT INTERFERE WITH CRANE OPERATION. 2. INSTALL TOP OF UNIT HEATER +/- 6" BELOW MEZZANINE.

AIR HANDLER UNIT

Table with columns: MARK, AIR DATA, COOLING COIL DATA, ELECTRICAL DATA, GENERAL DATA, MANUFACTURE, MODEL, NOTES

NOTES: 1. PROVIDE WITH A SECONDARY OVERFLOW SWITCH.

AIR COOLED CONDENSING

Table with columns: MARK, SERVES, NOMINAL CAPACITY, COOLING DATA, CONDENSING DATA, ELECTRICAL DATA, GENERAL DATA, MANUFACTURE, MODEL, NOTES

NOTES: 1. REFRIGERANT PIPING QUANTITIES AND SIZE TO BE PER MANUFACTURER'S SCHEMATIC. 2. COOLING CAPACITY BASED ON 95°F EAT. 3. PROVIDE FACTORY COMPUTER SELECTION PRINTOUT FOR CONDITION STATED ABOVE.

PACKAGE TERMINAL AIR CONDITIONAL UNIT

Table with columns: MARK, NOMINAL CAPACITY, COOLING DATA, ELECTRICAL DATA, GENERAL DATA, MANUFACTURE, MODEL, NOTES

NOTES: 1. REFRIGERANT PIPING SHALL BE SIZED BY MANUFACTURER. 2. PROVIDE FACTORY COMPUTER SELECTION PRINTOUT FOR CONDITION STATED ABOVE. 3. PROVIDE COMPRESSOR WITH 5 YEAR WARRANTY. ALL COMPRESSORS SHALL HAVE A MINIMUM SEER VALUE OF 17.0.


BOILER SCHEDULE

Table with columns: UNIT, MFG, MODEL NO., INPUT, OUTPUT, THERMAL, GAS, IN/OUT, VENT, INTAKE, ELECTRICAL, SHIPPING, REMARKS

REMARKS: 1. INCLUDE CONDENSATE NEUTRALIZATION KIT. 2. PRIMARY BOILER PUMPS INTEGRAL TO BOILERS. 3. BOILER INCLUDES INTEGRAL MODULES. 4. BOILER FLUE SHALL BE AL-29 OR EQUAL. 5. HEATING CAPACITY BASED ON 75% WATER/ 25% PROPYLENE GLYCOL.



MECHANICAL SCHEDULES & DETAILS (1 OF 2)




PIPE HANGER DETAIL

SCALE: NONE


ELECTRICAL CLEARANCE SPACE

SCALE: NONE
1. VERIFY WITH LOCAL CODE REQUIREMENTS, SPECIFICATIONS AND NATIONAL ELECTRIC CODE




UNIT HEATER PIPING DETAIL

SCALE: NONE
1. AUTOFLOW CONTROL VALVES SHALL INCLUDE INTEGRAL AIR BLEEDERS, TEST PORTS AND UNIONS.




CABINET UNIT HEATER DETAIL

SCALE: NONE
1. AUTOFLOW CONTROL VALVES SHALL INCLUDE INTEGRAL AIR BLEEDERS, TEST PORTS AND UNIONS.




ROOF AND WALL CAP DETAIL

SCALE: NONE




BASE MOUNTED PUMP DETAIL

SCALE: NONE
1. PUMPS SHALL BE PROVIDED WITH LASER ALIGNMENT COMPLETED ON SITE. PROVIDE ALIGNMENT REPORT WITH PUMP CLOSEOUT O&M MANUALS.




HEATING EXPANSION TANK DETAIL

SCALE: NONE




IN-FLOOR HEAT MANIFOLD DETAIL

SCALE: NONE



WATER COIL WITH 2-WAY VALVE DETAIL


SCALE: NONE



WATER COIL WITH 3-WAY VALVE DETAIL

SCALE: NONE






- NOTES:
1. THIS DRAWING IS MEANT TO DEMONSTRATE SYSTEM PIPING CONCEPT ONLY.
 2. INSTALLATIONS MUST COMPLY WITH ALL LOCAL CODES.
 3. INSTALL A MINIMUM OF 12 DIAMETERS OF STRAIGHT PIPE UPSTREAM OF ALL CIRCULATORS.
 4. INSTALL A MINIMUM OF 6 DIAMETERS OF STRAIGHT PIPE UP AND DOWNSTREAM OF ALL CLOSELY SPACED TEES.
 5. PIPING SHOWN IS PRIMARY/SECONDARY.
 6. RECOMMENDED: GAS REGULATOR (AND IS REQUIRED WHEN SUPPLY PRESSURE IS GREATER THAN 20" WC).
 7. MANDATORY: BOILER STRAINER (20 MESH OR FINER).



BOILER PIPING DETAIL

SCALE: NONE







NOT DISCLOSED



LEGEND

SYMBOL	ABBREVIATION	DESCRIPTION
—	CW	COLD WATER
—	HW	HOT WATER
—	RHW	RECIROULATED HOT WATER
—	TW	TEMPERED WATER
—	SCW	SOFT COLD WATER
—	SHW	SOFT HOT WATER
—	SRHW	SOFT RECIROULATED HOT WATER
—	DI	DEIONIZED WATER
—	LSPR	LAWN SPRINKLER
—	FSPR	FIRE SPRINKLER
—	A	COMPRESSED AIR
—	O	OXYGEN
—	VAC	VACUUM
—	W	WASTE BELOW GRADE
—	W	WASTE BELOW FLOOR
—	W	WASTE ABOVE GRADE
—	AW	ACID WASTE
—	DS	DOWNSPOUT (RAINWATER)
—	V	VENT
—	AV	ACID VENT
—	HWS	HEATING WATER SUPPLY
—	HWR	HEATING WATER RETURN
—	CHS	CHILLED WATER SUPPLY
—	CHR	CHILLED WATER RETURN
—	COND	CONDENSATE
—	G	NATURAL GAS LINE (FIRM)
—	WG	WELDING GAS

1. SHUT-OFF VALVE
2. PRESSURE REDUCING VALVE
3. BALANCE VALVE
4. CHECK VALVE
5. CONTROL VALVE
6. GAS COCK/PLUG VALVE
7. THERMOSTAT
8. PRESSURE GAUGE
9. MANUAL AIR VENT
10. UNION
11. STRAINER/WIRDRAN VALVE
12. TOP CONNECTION TEE W/ WELBOW
13. BOTTOM CONNECTION TEE W/ WELBOW
14. SIDE CONNECTION TEE
15. SHOCK ABSORBER
16. FLOW METER FITTING
17. PIPE ANCHOR
18. BALANCE VALVE W/ LOW METER FITTING
19. FLOW CONTROL VALVE
20. PIPE CAP, PLUG OR CLEANOUT
21. FLOAT AND THERMOSTATIC TRAP
22. PRESSURE AND TEMPERATURE TEST PORT
23. FLOW DIRECTION ARROW
24. EXPANSION JOINT
25. FLEX CONNECTOR
26. PRESSURE AND TEMPERATURE RELIEF VALVE
27. THREE WAY CONTROL VALVE
28. CONTINUATION SYMBOL
29. PIPE DOWN
30. PIPE UP



WATER HEATER SCHEDULE

UNIT NO.	MPG.	MODEL NO.	CAPACITY (GALLONS)	INPUT (MBH)	EFFICIENCY	RECOVERY @ 90° RISE	EXPANSION TANK	ELECTRICAL VPH FLA	SHIPPING WEIGHT (LBS)	REMARKS	
WHTR-1	A.O. SMITH	BTH-150	100	150	97	198	A.O. SMITH PM-14	1201	5.0	523	1,2,3
WHTR-2	A.O. SMITH	BTH-150	100	150	97	198	A.O. SMITH PM-14	1201	5.0	523	1,2,3
WHTR-3	A.O. SMITH	ENL-50	48	4500W	0.93	21	A.O. SMITH PM-14	2401	21	172	1,4,5,7
WHTR-4	A.O. SMITH	E-CT-20	19.9	2500	0.93	11	A.O. SMITH PM-14	1201	15	60	1,5,6,7

REMARKS:
1. ASME TRP RELIEF VALVE.
2. INCLUDE OPTIONAL CONDENSATE NEUTRALIZATION KIT.
3. CONCENTRIC VENT KIT.
4. UNIT SHALL BE MOUNTED ON A HOLDRITE MODEL 50-SWHP-W-C WATER HEATER PLATFORM.
5. UNIT SHALL BE MOUNTED ABOVE LAVATORY.
6. UNIT SHALL BE MOUNTED ON A HOLDRITE MODEL 40-SWHP-W-C WATER HEATER PLATFORM.
7. PROVIDE ADEQUATE BACKING AND STRUCTURAL SUPPORT TO PROPERLY SUPPORT THE OPERATING WEIGHT OF THE WATER HEATER.

PUMP SCHEDULE


UNIT NO.	MPG.	DESCRIPTION	MODEL NO.	STYLE	FLOO RATE (GPM)	HEAD (FT)	ROTOR HP	RPM	ELECTRICAL VPH FLA	REMARKS	
P-21	TACO	DOMESTIC HOT WATER RECIC	0012	INLINE	5	14	1/8	3250	120	1	1,2
P-22	TACO	DOMESTIC HOT WATER RECIC	0010	INLINE	5	10	1/8	3250	120	1	1,2
P-23	TACO	DOMESTIC HOT WATER RECIC	0010	INLINE	5	10	1/8	3250	120	1	1,2

REMARKS:
1. PUMPS SHALL INCLUDE BRONZE OR STAINLESS STEEL FLANGES WITH INTEGRAL FLOW CHECKS AND ASSOCIATED GASKETS.
2. PUMPS SHALL BE MOUNTED IN A MANNER THAT ALLOWS THEM TO BE EASILY SERVICED AND/OR REPLACED.
3. DOMESTIC RECIROULATING PUMPS SHALL INCLUDE ALL ASSOCIATED FLANGES, CHECK VALVES, AQUASTAT AND TIMER.

PLUMBING FIXTURE SCHEDULE



FIXTURE SYMBOL	TYPE	MPG.	MODEL NO.	TRIM	SUPPLIES	WASTE	REMARKS
WC-1	WATER CLOSET WALL HUNG FLUSH VALVE	KOHLER	K-4325 KINGSTON	SLOAN G2 8111.1-0 BATTERY OPERATOR SENSOR FLUSH VALVE	---	---	K-4731-SC TOILET SEAT INSTALL TOP OF BOWL RIM AT 15" A.F.F. DUAL FILTERED BY-PASS ON FLUSH VALVE
WC-2	WATER CLOSET WALL HUNG FLUSH VALVE - ADA	KOHLER	K-4325 KINGSTON	SLOAN G2 8111.1-0 BATTERY OPERATOR SENSOR FLUSH VALVE	---	---	K-4731-SC TOILET SEAT INSTALL TOP OF BOWL RIM AT 17" A.F.F. DUAL FILTERED BY-PASS ON FLUSH VALVE
WC-3	WATER CLOSET FLOOR MOUNTED FLUSH VALVE - ADA	KOHLER	K-3493 HIGHLINE	---	---	---	K-4731-SC TOILET SEAT
UR-1	URINAL - WALL MOUNTED	KOHLER	K-5016 DEXTER	SLOAN G2 8186-1.0 BATTERY OPERATOR SENSOR FAUCET	---	---	INSTALL TOP OF RIM AT 24" A.F.F. DUAL FILTERED BY-PASS ON FLUSH VALVE
UR-2	URINAL - WALL MOUNTED - ADA	KOHLER	K-5016 DEXTER	SLOAN G2 8186-1.0 BATTERY OPERATOR SENSOR FLUSH VALVE	---	---	INSTALL TOP OF RIM AT 17" A.F.F. DUAL FILTERED BY-PASS ON FLUSH VALVE
L-1	LAVATORY - DROP IN LAVINA - ADA	KOHLER	K-2196-1 PENNINGTON SINGLE HOLE	SLOAN 150-1.0 BATTERY OPERATOR SENSOR FAUCET	BRASSRAFT KTCR19 STOPS 5/20 SUPPLIES 648 ESCHUTZIONS	METAL GRID STAINER, 1 1/2" 17 GA. BRASS P-TRAP ASSEMBLY	---
L-2	LAVATORY - WALL HUNG CHINA - ADA	KOHLER	K-2207 KINGSTON SINGLE HOLE	SLOAN 150-1.0 BATTERY OPERATOR SENSOR FAUCET	BRASSRAFT KTCR19 STOPS 5/20 SUPPLIES 648 ESCHUTZIONS	METAL GRID STAINER, 1 1/2" 17 GA. BRASS P-TRAP ASSEMBLY	---
L-3	LAVATORY - WALL HUNG MULTIFONT	SLOAN	EW-43000	INTEGRAL SENSOR	BRASSRAFT KTCR19 STOPS 5/20 SUPPLIES 648 ESCHUTZIONS	METAL GRID STAINER, 1 1/2" 17 GA. BRASS P-TRAP ASSEMBLY	HARD WIRE. COORDINATE WITH ELECTRICAL. COORDINATE COLOR WITH ARCHITECT.
SK-1	SINK - STAINLESS STEEL SINGLE COMPARTMENT - ADA	ELKAY	CECR2521 GEBRITY 2-HOLE 4" C	ELKAY FAUCET LK496GN416 1.5 GPM AERATOR	BRASSRAFT KTCR19 STOPS 5/20 SUPPLIES 648 ESCHUTZIONS	CUP STYLE BASKET STAINER, 1 1/2" 17 GA. BRASS P-TRAP ASSEMBLY	WRIST BLADE HANDLES
EWC	WATER COOLER DUAL HEIGHT - ADA	ELKAY	EZ28TLC	---	BRASSRAFT KTCR19 STOPS 5/20 SUPPLIES 648 ESCHUTZIONS	17 GA. BRASS P-TRAP	---
SH-1	SHOWER - ADA	AQUATIC	1363FSC	---	---	2" SHOWER DRAIN ASSEMBLY	ADA COMPLIANT SEAT, STAINLESS STEEL GRAB BARS FLEXIBLE DAM, REMOVABLE THRESHOLD
MSK	MOP SINK	MUSTEE	8M	63 80GA FAUCET	---	2" SHOWER DRAIN	STAINLESS STEEL DOME STRAINER, MOP HANGER HOSE AND HOLDER, INSTALL CHECK VALVES ON HOT AND COLD WATER SUPPLY PIPING
ESH	EMERGENCY SHOWER	SPEAKMAN	SE-616	---	---	---	RECIROULATED TEMPERED WATER CONNECTION
UB-1	LAUNDRY BOX	GLY GRAY	WB200HA	---	---	---	SINGLE LEVER BALL TYPE VALVE WITH INTEGRAL HAMMER ARRESTORS. PROVIDE CHECK VALVES ON HOT AND COLD WATER SUPPLY TO LAUNDRY BOX
WH	WALL HYDRANT	WOODFORD	MODEL 67	---	---	---	INTEGRAL VACUUM BREAKER, LOOSE KEYS OPERATOR, COORDINATE LENGTH WITH WALL DEPTH SEAL WALL PENETRATION WITH FOAM SEALANT
FD-1	FLOOR DRAIN	SILOX CHIEF	832-NR SERIES	---	---	3"	NICKEL BRONZE STRAINER. PROVIDE LEVELING SHIMS AS NEEDED
FD-2	FLOOR DRAIN	SILOX CHIEF	860-4P SERIES	---	---	4"	CAST IRON ROUND STRAINER
FD-3	FLOOR DRAIN	SILOX CHIEF	860-4P SERIES	---	---	4"	CAST IRON ROUND STRAINER & STAINLESS STEEL DEBRIS BASKET
CD	FLOOR CLEANOUT	SILOX CHIEF	834 SERIES	---	---	4"	NICKEL BRONZE COVER. PROVIDE LEVELING SHIMS AS NEEDED
GCD	GRADE CLEANOUT	SILOX CHIEF	851-24 SERIES	---	---	4"	CAST IRON ROUND COVER
TD-1	TRENCH DRAIN	ACO	5300K	---	---	---	12" DUCTILE IRON SLOTTED GRATE, IRON EDGED CHANNELS
TD-2	TRENCH DRAIN	ACO	5300K	---	---	---	SILOX INLINE CATCH BASIN AND OPTIONAL TRASH BUCKET
TMV	THERMOSTATIC MIXING VALVE	LAWLER	803	ROUGH BRASS	---	---	MOUNT MIXING VALVE ON WALL 5' A.F.F.
DMV	EMERGENCY MIXING VALVE	LAWLER	911	ROUGH BRASS	---	---	RECESSED STAINLESS STEEL CABINET INSTALLED 5' A.F.F. 85" SET POINT
RD-1	ROOF DRAIN ASSEMBLY	ZURN	2100	---	---	4"	CAST IRON DOME AND STRAINER OBTAIN WRITTEN ROOF DRAIN HEIGHTS FROM ROOFING CONTRACTOR PRIOR TO INSTALLATION
RD-2	ROOF DRAIN ASSEMBLY	ZURN	2100	---	---	6"	CAST IRON DOME AND STRAINER OBTAIN WRITTEN ROOF DRAIN HEIGHTS FROM ROOFING CONTRACTOR PRIOR TO INSTALLATION
ORD-1	OVERFLOW ROOF DRAIN ASSEMBLY	ZURN	2100	---	---	4"	CAST IRON DOME AND STRAINER PROVIDE 2" INTERNAL WATER DAM OBTAIN WRITTEN OVERFLOW ROOF DRAIN HEIGHTS FROM ROOFING CONTRACTOR PRIOR TO INSTALLATION
ORD-2	OVERFLOW ROOF DRAIN ASSEMBLY	ZURN	2100	---	---	6"	CAST IRON DOME AND STRAINER PROVIDE 2" INTERNAL WATER DAM OBTAIN WRITTEN OVERFLOW ROOF DRAIN HEIGHTS FROM ROOFING CONTRACTOR PRIOR TO INSTALLATION

REMARKS/NOTES:
1. ALL FIXTURES INCLUDING FAUCET TRIM AND SHOWER HEADS SHALL BE CALKED. TOILET AND OTHER FIXTURES LOCATED AGAINST TILE SHALL BE CALKED WITH CLEAR CALK.
2. ALL FIXTURES SHALL BE INSTALLED AS RECOMMENDED BY THE MANUFACTURER INCLUDING MORTAR BEDS/ADHESIVE FOR SHOWERS IF RECOMMENDED.
3. COORDINATE FLOORING AND THRESHOLD HEIGHT REQUIREMENTS FOR ADA SHOWERS WITH THE GENERAL CONTRACTOR PRIOR TO ASSOCIATED WORK.
4. SHOWER DRAINS SHALL BE INSTALLED WITH 100% SILICONE SEALANT. COMPRESSION STYLE SHOWER DRAINS ARE NOT ACCEPTABLE FOR THIS PROJECT.
5. THE INTEGRITY OF THE FIRE RATED WALL AND CEILING SHALL BE MAINTAINED AT ALL TIMES. THIS CONTRACTOR IS RESPONSIBLE FOR FIRE CALKING/SEALING AS REQUIRED TO COMPLETE THEIR SCOPE OF WORK.
6. THE FIXTURE STOPS AND SUPPLIES LISTED ABOVE SHALL BE CHROME PLATED 1/4" TURN BALL STYLE STOPS WITH CHROME METAL ESCHUTZIONS TRIM RINGS (CALKED TO WALL) AND FLEXIBLE BRAIDED SUPPLY TUBES.
7. INSTALL ALL ADA FIXTURES PER MANUFACTURERS RECOMMENDED HEIGHTS AND LOCATIONS AS ALLOWED BY LOCAL ADA CODE.




ABBREVIATION DESCRIPTION

COMP	Compressed Air	HPS	Heat Pump Supply
AFF	Above Finished Floor	HTG	Hot Water
AG	Above Grade	HW	Heating Water Return
AHL	Air Handling Unit	HWR	Heating Water Return
ARCH	Architect or Architectural	HWS	Heating Water Supply
AV	Acid Vent	INT	Inside Dimension
AW	Acid Waste	INT	Internal
BAV	Building Automation System	IE	Invert Elevation
BS	Below Grade	KW	Kilowatt
BMP	Brake Masterpower	LF	Laboratory
BTP	Brake Thermal Units	LES	Weight in Pounds
CA	Combustion Air	LP	Liquid Petroleum
CAP	Center of Center	LSPR	Lawn Sprinkler
CC	Center of Center	LWT	Leaving Water Temperature
CC	Chilled Water Return	MEG	Manufacturer
CHS	Chilled Water Supply	MBH	BTU x 1000
CO	Cleaned	MHP	Moist Horsepower
COND	Condensate	MSK	Mop Sink
CNH	Cabinet Unit Heater	MTR	Mounted
CW	Cold Water	NO	Number
DI	Diameter	OC	On Center
DN	Down	OD	Outside Diameter
DS	Downspout	ODS	Overflow Downspout
DS	Down	ORD	Overflow Roof Drain
DS	Down	PD	Pressure Drop
EEW	Emergency Eye Wash	PH	Phase
ELECT	Electrical	PUMP	Pumping
EQUIP	Equipment	RAD	Radiant Heater/Radiation
ESN	Emergency Shower	RD	Recirculating
EWC	Electric Water Cooler	RO	Recirculating
EW	Entering Water Temperature	RCR	Revolutions Per Minute
EXIST	Existing	RPM	Revolutions Per Minute
EXP	Expansion	SH	Shower
FCU	Fan Coil Unit	SK	Sink
FD	Floor Drain	SPFCS	Specifications
FP	Fan Powered VAV	SS	Stainless Steel
FSK	Floor Sink	TEMP	Temperature
FSR	Fine Sprinkler	TW	Tempered Water
FTG	Fitting	TYP	Typical
FTG	Fitting (Natural or LP Gas)	UH	Unit Heater
GAL	Gallon	UV	Unit Ventilator
GALV	Galvanized	V	Vent
GPH	Gallons Per Hour	VAC	Vacuum
GPM	Gallons Per Minute	VOL	Volume
HANDI	Handicapped	W	Waste or Waste
HC	Heating Coil	WI	With (to include)
HD	Hot-Drain	WO	Without (does not include)
HP	Horsepower	WC	Water Closet
HPR	Heat Pump Return	WF	Wash Facility
		WPD	Water Pressure Drop
		WG	Weld Gas




PLUMBING DETAILS AND SCHEDULES




KEYED PLUMBING NOTES: (X)


1. 4" W UP TO CO.
2. 4" W UP TO CARRIER GROUP.
3. 4" W UP TO FD-2.
4. 4" W UP TO TD-2/CATCH BASIN.
5. 4" W UP TO GCO.
6. 3" W UP TO FD-1.
7. 3" W UP TO MSK.
8. 2" W UP TO UR.
9. 2" W UP TO LAV.
10. 2" W UP TO SK.
11. 2" V UP.
12. 2" W UP TO EWC.
13. 2" W UP TO SH, 2" V UP.
14. 2" V UP, 2" W UP TO SH.
15. 2" W UP TO LAV, 2" V UP.
16. 2" V UP, 2" W UP TO LAV/EWC.
17. SEE SHEET P1.3 FOR CONTINUATION.
18. 6" FSPR UP TO BLIND FLANGE, 2 1/2" CW SERVICE UP TO BLIND FLANGE, PROVIDE THRUST BLOCKING. SEE DETAIL ON SHEET P1.1.
19. 4" W UP TO FD-3.




WASTE & VENT RISER
SCALE: NONE




WASTE & VENT RISER
SCALE: NONE



WASTE & VENT RISER
SCALE: NONE



NOT DISCLOSED




KEYED PLUMBING NOTES: (X)


1. 4" W UP TO CO.
2. 4" W UP TO WC.
3. 4" DRAIN UP TO TD (LESS P-TRAP).
4. 2" W UP TO LAV.
5. 2" W UP TO SK.
6. 2" V UP, 2" V UP.
7. 2" V UP.
8. TRENCH DRAIN ASSEMBLY. REFER TO TRENCH DRAIN JOINT DETAIL ON SHEET P1.1.
9. SAND/OIL INTERCEPTOR (1,250 GAL/MIN). SEE DETAIL ON SHEET P1.1.
10. 2" W UP TO UR.
11. SEE SHEET P-3 FOR CONTINUATION.
12. 4" W UP TO FD-2.
13. 2" V UP, 2" V UP, 2" V UP, 2" W UP.
14. 4" DRAIN UP TO CO.
15. 4" W UP TO FD-3.
16. SAND/OIL INTERCEPTOR (300 GAL/MIN). SEE DETAIL ON SHEET P1.1.

NOT DISCLOSED

**UNDERGROUND
PLUMBING
PLAN - SOUTH**




Printed On:




KEYED PLUMBING NOTES:


1. 3/4" CW DN TO WH MOUNTED 18" ABOVE FINISHED GRADE.
2. 1/2" HW DN, 1/2" CW DN, 1 1/2" V/2" W DN, ROUTE PIPING THROUGH CABINET TO SERVE SK-1.
3. 2" V UP (4" VTR), 2" V DN.
4. 2" V UP (4" VTR).
5. 2" V DN, 1/2" CW DN.
6. 1 1/2" V/2" W DN, 1/2" CW DN, 1/2" HW DN.
7. 1/2" CW DN, 1/2" HW DN, 1 1/2" V/2" W DN.
8. NATURAL GAS METER SIZED AT 2 PSIG @ 1 PSIG PRESSURE DROP X 500' @ 9130 MBH.
9. FIRE DEPARTMENT CONNECTION LOCATION.
10. 6" DS DN, 6" ODS DN, ROUTE PIPING DN AND OUT THROUGH WALL 18" ABOVE FINISHED GRADE.
11. 4" ODS UP TO 4" ORD.
12. 4" DS UP TO 4" RD.
13. 4" ODS DN AND OUT THROUGH WALL 18" ABOVE FINISHED GRADE.
14. 4" DS DN AND OUT THROUGH WALL 18" ABOVE FINISHED GRADE.
15. 6" DS UP TO 6" RD.
16. 6" ODS UP TO 6" ORD.
17. ROUTE PIPING THROUGH CABINET TO SERVE COFFEE MAKER, COFFEE MAKER WATER PIPING SHALL HAVE AN INDEPENDENT ISOLATION VALVE LOCATED UNDER SK-1.
18. SEE SHEET P1.5 FOR CONTINUATION.
19. SEE THIS SHEET FOR CONTINUATION.
20. 2" V DN, 1/2" CW DN, 1/2" 140" HW DN.
21. 3/4" G DN TO WHTR (TYPICAL OF 2), PROVIDE GASCOCK, PRESSURE REDUCING VALVE, DIRT LEG AND UNION.
22. 100 GALLON NON-ASME GAS FIRED WATER HEATERS ON CONCRETE HOUSEKEEPING PAD. SEE WATER HEATER PIPING DETAIL ON SHEET P1.1, HOUSEKEEPING PAD BY OTHERS.
23. 1/2" CW DN, 1/2" HW DN, 1 1/2" V/2" W DN, 1/2" HW DN, 1/2" CW DN.
24. 2" V DN.
25. 1" CW DN, 2" V DN, 1 1/2" V/2" W DN, 3/4" CW DN.
26. 2" V DN, 4" V UP/DN, 2" V DN.
27. 1" CW DN, 2" V DN, 1" CW DN.
28. 1" CW DN.
29. 4" V UP/DN (4" VTR).
30. 1" CW DN, 1 1/2" V/2" W DN, 3/4" CW DN, 1 1/2" V/2" W DN, 3/4" CW DN.
31. 1/2" CW DN, 1/2" HW DN, 1 1/2" V/2" W DN, 3/4" CW DN, 3/4" HW DN.
32. 1/2" CW DN, 1/2" HW DN.
33. 1/2" HW DN, 1/2" CW DN.
34. 1 1/2" V/2" W DN, 3/4" CW DN.
35. 1/2" CW DN, 1/2" HW DN, 1 1/2" V/2" W DN, 2" V DN.
36. 2" V DN, 1 1/2" V/2" W DN, 1/2" CW DN, 1/2" HW DN.
37. 2" V DN, 2" V UP (4" VTR).
38. 2 1/2" WATER TO METER AND REDUCED PRESSURE BACKFLOW PREVENTER.
39. FIRE SPRINKLER RISER.
40. 4" VTR.




ENLARGED MECHANICAL ROOM PLAN
SCALE: NONE



ENLARGED RESTROOM PLAN
SCALE: NONE





ENLARGED RESTROOM PLAN
SCALE: NONE



ENLARGED RESTROOM PLAN
SCALE: NONE

NOT DISCLOSED





- KEYED PLUMBING NOTES:** (X)
- 2" V DN, 2" V DN.
 - 2" V UP (4" VTR), 2" V UP (4" VTR).
 - 1 1/4" TW DN, 2" V DN, 2" V DN, 2" V DN, 1 1/2" V/2" W DN, 3/4" HW DN, 3/4" CW DN.
 - 1 1/4" HW DN, 1 1/2" TW DN, 1 1/4" CW DN, REDUCE 1 1/2" TW TO 1 1/4" AT EMV.
 - 3/4" A DN, 3/4" CW DN TO HB, MOUNT AIR AT 48" A.F.F. AND HB 36" A.F.F. PROVIDE (2) 1/2" QUICK CONNECT COUPLINGS, DRIP LEG AND DRAIN DOWN VALVE.
 - 3/4" CW DN TO WH MOUNTED 18" ABOVE FINISHED GRADE.
 - SEE SHEET P1.4 FOR CONTINUATION.
 - 2" V UP (4" VTR).
 - 3/4" A DN, MOUNT AIR AT 48" A.F.F. PROVIDE (2) 1/2" QUICK CONNECT COUPLINGS, DRIP LEG AND DRAIN DOWN VALVE.
 - 1 1/2" V/2" W DN, 1/2" HW DN, 1/2" CW DN.
 - 1 1/2" V/2" W DN, 3/4" CW DN.
 - 1 1/2" V/2" W DN, 1/2" CW DN, 1/2" HW DN.
 - 1/2" CW DN, 2" V DN, 2" V DN, 1 1/2" V/2" W DN, 1/2" HW DN, 1/2" CW DN.
 - 1" G DN, 3/4" A DN, 1" CW DN, TERMINATE DROPS 5' A.F.F. WITH FULL PORT BALL VALVE AND QUICK CONNECT FITTINGS TO MATCH THE PRESSURE WASHER CONNECTION REQUIREMENTS. COORDINATE WITH MANUFACTURER AND OWNER TO DETERMINE EXACT CONNECTION REQUIREMENTS AND LOCATIONS. PROVIDE WITH GAS COCK AND PRESSURE REDUCING VALVE.
 - 1/4" CW WITH ISOLATION VALVE UNDER COUNTER FOR COFFEE MACHINE.

NOT DISCLOSED

